

DOSATRON[®]

WATER POWERED DOSING TECHNOLOGY

The Diaphragm Dosatron? Water power at the very first day

DIA 4 RE

Available in January 2011

Very low water flow (less than 5 l/h) : For weaners or small numbers.

More capacity as they grow (up to 2 500 l/h) : For production up to 5 000 weaners or 2 000 finishers.

Can work at very low water pressure (header tanks) : From 0.15 Bar – 1.5 m height up to 4 Bar.

No metal part in the motor with an external injection of the treatments : To prevent from chemical corrosion. Easy preventive maintenance of wearing parts.

Easy to adjust : 1 to 4 %.

High dosage possibility (4 % - 1:25) allowing better solubility when using powders.

Ø 12 mm suction hose to limit clogging risk.



Water power at the very first day

DOSATRON INTERNATIONAL S.A.S.

without prior notice.. © DOSATRON INTERNATIONAL S.A.S. 2010

33370 TRESSES (BORDEAUX) - FRANCE Tel. 33 (0)5 57 97 11 11 - Fax. 33 (0)5 57 97 11 29 / 10 85 e.mail : info@dosatron.com - http://www.dosatron.com This document does not form a contractual engagement on the part of Dosatron International and is for information only. Dosatron International reserves the right to alter product specification or appearance

DOSATRON